

UNIX essentials (hands-on)

- the directory tree
- running programs
- the shell
 - command line processing
 - special characters
 - command types
 - shell variables
 - environment variables
 - wildcards
 - shell scripts
 - shell commands
 - pipes and redirection
- OS commands
- special files

- **The Directory Tree**

- directories contain files and/or directories

- / : means either the root directory, or a directory separator

- consider the directory `/home/user/AFNI_data1`

- class work:

- open a terminal window
 - commands: `pwd`, `ls`, `ls -a`, `ls -al`
 - use the "`cd`" command to go to the given directories
 - e.g. for directory `/usr/bin`, use the command: `cd /usr/bin`
 - once there, use the commands "`pwd`", "`ls`", and "`ls -al`"
 - note that you can always return to the home directory via: `cd`

- `/, home, user, AFNI_data1, .., AFNI_data1/afni, ../..`

- `/home/user, /usr/bin, ~/abin, ../../home/user/../user/../user`

- many commands can be used to return to the home directory (of "user")

- examples: `cd`, `cd ~`, `cd ~user`, `cd $HOME`, `cd /home/user`

- an "absolute" pathname begins with '/', a "relative" pathname does not

- a relative pathname depends on where you start from
 - in the directories above, note which are relative pathnames

→ every directory has a parent directory

- the relative pathname for the parent directory is '..'
- the relative pathname for the current directory is '.'

→ commands:

```
ls, ls -a, ls -al, ls -alt, ls -altr, cd ~/AFNI_data1/afni  
ls -l, wc ideal_r1.1D, cat idea_r1.1D, less ideal_r1.1D
```

→ 'less': a file perusal program

- basic keystrokes while running less: *Enter*, *Space*, *b*, *g*, *G*, *h*, *q*
- command: `less rall_vr+orig.HEAD`

• Programs

→ a program is something that gets "executed", or "run"

→ the first element of a command line is generally a program

→ commands:

```
echo the home directory of $USER is $HOME  
ls ~ ~/AFNI_data1 ~/AFNI_data1/afni/ideal_r1.1D
```

→ script: an interpreted program (interpreted by another program)

- e.g. consider the `c00.all` script: `cat ~/AFNI_data1/ht03/c00.all`

- **The Shell: command line processing**

- command interpreter (case and syntax sensitive)

- examples: `tcsh`, `csch`, `sh`, `bash`, `ksh`, `zsh`, `wish`, `tclsh`, `rsh`,
`ssh`

- command: `echo $SHELL`

- **The T-shell: `/bin/tcsh`**

- an enhanced C-shell (`csch`), which has C programming style syntax

- command line processing, simplified outline:

- evaluate special characters, such as:

- `~ ! @ # $: & () * ? \ ' " ` [] | { }`

- decide which program(s) to execute

- full pathname, alias, shell command, search the `$PATH`

- execute appropriate program, giving it the parameter list

- save the execution status in the `$status` variable

- command: `ls $HOME ~/suma_demo '$pickle'`

- `tcsh` has automatic filename completion using the `Tab` key

- type `ls suma` and hit the `Tab` key, watch what happens, and hit `Enter`

- type `ls AF` and hit the `Tab` key, note what happens

- **Special Characters**

~ : the current user's home directory (e.g. /home/user)

\$: used to access a variable (e.g. \$home)

& : used to put a command in the background (e.g. afni &)

* : wildcard, matching zero or more characters (e.g. ls AFNI_d*)

? : wildcard, matching exactly one character (e.g. ls AFNI_data?)

\ : command line continuation (must be the last character on the line)

' : the shell will not evaluate special characters contained within these quotes
(e.g. echo '\$HOME' gives \$HOME, not /home/user)

" : the shell will evaluate \$variables and `commands` contained within these
(e.g. echo "[*] my home dir is \$HOME")

(e.g. echo "the numbers are 'count -digits 2 7 12'")

` : execute the command contained within these quotes, and replace the quoted part with the output of the contained command

(e.g. echo "the numbers are `count -digits 2 7 12`")

- **Command Types**

→ consider the commands:

```
/bin/ls ~
```

```
ls ~
```

```
cd ~
```

```
wc ~/AFNI_data1/afni/ideal_r1.1D
```

→ the "which" command shows where the shell gets a command from:

```
which ls
```

```
which cd
```

```
which wc
```

→ the shell must decide what type of command it has:

- full pathname for a program: execute that program
- alias: apply any alias(es) then start over (decide on which program to run)
- shell command: part of the `/bin/tcsh` program
- check the `$PATH` directories for the program

- **The PATH Variable**

→ a list of directories to be searched for a given program to be run from

→ the `$path` and `$PATH` variables are identical, but are represented differently

→ commands: `echo $PATH`

```
echo $path
```

```
cat ~/.cshrc
```

- **Shell Variables**

- shell variables are variables that are stored in, and affect the shell
- all variables are stored as strings (or as arrays of strings)
- a variable is accessed via the '\$' character
- the 'echo' command: echo the line after processing any special characters
 - command: `echo my home dir, $HOME, holds ~/*`
- the 'set' command: set or assign values to one or more variables
 - without arguments: 'set' displays all variables, along with any values
 - 'set' takes a list of variables to set, possibly with values
 - consider the commands:

```
set food
echo $food
set food = pickle
echo $food
echo $pickle
set eat food = chocolate donut
set
set food = "eat chocolate donut"
echo $food
```

→ variables can be assigned the result of a numerical computation using the '@' command, however only integer arithmetic is allowed

- commands:

```
set value1 = 17
@ value2 = $value1 * 2 + 6
echo value2 = $value2
```

• Array Variables

→ array variables are set using ()

→ consider the commands:

```
set stuff = ( 11 12 13 seven 15 )
echo $stuff
echo $stuff[1]
echo $stuff[2-4]
echo $stuff[8]
set stuff = ( hi $stuff $food )
echo $stuff
echo $path
cat ~/.cshrc
```


- **Environment Variables**

- similar to shell variables, but their values will propagate to children shells
- by convention, these variables are all upper-case (though it is not required)
- similarly, shell variables are generally all lower-case
- set environment variables using "`setenv`" (as opposed to the "`set`" command)
- without any parameters, the "`setenv`" command will display all variables
- the "`setenv`" command will only set or assign one variable at a time
- the format for the command to set a value is (without any '=' sign):

```
setenv VARIABLE value
```

- commands:

```
setenv MY_NAME Elvis
```

```
echo $MY_NAME
```

```
echo $path
```

```
echo $PATH
```

```
echo $HOME
```

```
setenv
```

- **Wildcards**

→ used for shell-attempted filename matching

→ special characters for wildcards:

`*`, `?`, `[`, `]`, `^`

`*` : matches any string of zero or more characters

(special case: a lone `*` will not match files starting with `'.'`)

`?` : matches exactly one character

`[]` : matches any single character within the square brackets

`[^]` : matches any single character EXCEPT for those within the brackets

→ commands (run from the `~/AFNI_data1/SPGR_anat` directory):

```
ls
```

```
ls *
```

```
ls -a
```

```
ls I.*
```

```
ls I.04?
```

```
ls I.0[123]*
```

```
ls I.0[^123]*
```

```
echo I.0[^123]*
```

• Shell Scripts

→ a text file, a sequence of shell commands

→ the '\' character can be used for line continuation (for readability)

- for that purpose, it must be the last character on the line (including spaces)

→ executing shell scripts, 3 methods:

`tcsch filename` : execute filename as t-shell commands

`./filename` : execute filename according to the top `"#!program"`

➤ if no such line, use the current shell

➤ the file must have execute permissions (see `'ls -l'`)

`source filename` : execute filename using current shell

➤ this method affects the current environment, so it should be used only when that is the intention (e.g. `.cshrc`)

→ consider `~/AFNI_data1/ht03/c00.all`

→ consider `~/AFNI_data1/ht03/@stim_analyze`

→ use the command `"nedit my.script"` to create a script with a few commands

```
echo hello there
```

```
ls -a
```

```
cd $HOME/AFNI_data1
```

```
ls -al
```

→ run the script using the command: `tcsch my.script`

- **Some Shell Commands** (handled by the shell)

`cd` : change working directory
`echo` : echo command line to the terminal window
`pwd` : echo the present working directory
`set` : set variables or assign string values to variables
`@` : set a variable to the results of an integral computation
`alias` : display or create an alias
(e.g. `alias hi 'echo hello there'`)
`bg` : put a process in the background (usually after ctrl-z)
`fg` : put a process in the foreground
`exit` : terminate the shell
`setenv` : set environment variables
`source` : execute a script within the current shell environment

- special keystrokes (to use while a process is running)

`ctrl-c` : send an interrupt signal to the process
`ctrl-z` : send a suspend signal to the process

- **More Shell Commands: basic flow control**

→ commands: `if`, `else`, `endif`, `while`, `end`, `foreach`

```
if ( $user == "elvis" ) then
    echo 'the king lives!'
endif
```

```
set value = 5
set fact = 1
while ( $value > 0 )
    @ fact = $fact * $value
    @ value -= 1
end
echo 5 factorial = $fact
```

```
foreach value ( 1 2 3 four eight 11 )
    echo the current value is $value
end
```

```
foreach file ( I.*3 )
    ls -l $file
end
```

• Pipes and Redirection

> : redirect program output (stdout) to a file

e.g. `waver -help > waver.help`

`waver -pickle > waver.help`

>& : redirect all output (both `stdout` and `stderr`) to a file

e.g. `waver -pickle >& waver.pickle`

e.g. `tcsh my.script >& script.output`

>> : append program output to a file

| : pipe standard output to the input of another program

e.g. `3dDeconvolve -help | less`

|& : include `stderr` in the pipe

e.g. `tcsh my.big.script |& tee script.output`

- run the script
- send all output to the tee program
- the tee program duplicates the input, sending the output to both the terminal and the given file (`script.output`)
- you can see the output, but it is also stored for future analysis

- **Some OS Commands**

`ls` : list the contents of a directory

* `cat` : concatenate files to the terminal (print them to the screen)

* `more` : a file perusal program - view files one page at a time

* `less` : a better file perusal program (type `less`, get `more`)

`man` : on-line manuals for many OS commands (and library functions)

- this uses a "`less`" interface to display the information

- e.g. consider `man on : ls, less, man, tcsh, afni`

`info` : a new program to replace the "`man`" program

* `head` : display the top lines of a file (default = 10)

- e.g. `3dDeconvolve -help | head -25`

* `tail` : display the bottom lines of a file (default = 10)

- e.g. `tail ideal_r1.1D`

* `wc` : word count - count characters, words and lines (of a file)

`rm` : BE CAREFUL - remove files and/or directories (no recovery)

- e.g. `rm junk.file`

- e.g. `rm -r bad.directory`

* denotes a 'filter' program, which can take input from a file or from `stdin`

* `grep` : print lines from a file that match the given pattern

e.g. `grep path ~/.cshrc`

e.g. `ls ~/abin | grep -i vol`

e.g. from the output of "`3dVol2Surf -help`" show lines which contain 'surf', but not 'surface', then remove duplicates

```
3dVol2Surf -help | grep surf | grep -v surface | sort | uniq
```

- **Some Special Files (in the home directory)**

`.cshrc` : c-shell startup file ("csh run commands")

- set aliases
- adjust the path
- set shell and environment variables

`.afnirc` : **AFNI** startup file

`.sumarc` : **suma** startup file

`.login` : commands run at the start of a login shell (e.g. a terminal window)

`.logout` : commands run before exiting a login shell

`.tcshrc` : t-shell startup file (if it does not exist, the `.cshrc` file will be used)